



Intercom Harness

SV-HARNESS-INT (102791-000) Hook-up table

SV-HARNESS-INT LABEL	COLOR	FUNCTION	SV-INTERCOM-2S PIN	CONNECTION
10-30 VDC	RED	POWER	13	SHIP PWR (+)
GND	BLACK	GROUND	1	SHIP GND (-)
RADIO AUDIO INPUT	WHT	RADIO AUDIO INPUT (HIGH)	14	SV-COM-425 Pin 10
	WHT/BLU	RADIO AUDIO INPUT (LO)	GND	SV-COM-425 Pin 9
	SHLD	NO CONNECTION	GND	NO CONNECTION
RADIO MIC OUT	RED	RADIO MIC OUTPUT	25	SV-COM-425 Pin 1
	BLU	MIC GND	GND	SV-COM-425 Pin 2
	YLW	RADIO MIC PTT OUTPUT	12	SV-COM-425 Pin 5
	SHLD	NO CONNECTION	GND	NO CONNECTION
PILOT PHONES	RED	PILOT RIGHT	22	PILOT PHONE JACK
	YLW	PILOT LEFT	9	
	BLU	PILOT GND	GND	
	SHLD	NO CONNECTION	GND	NO CONNECTION
COPILOT PHONES	RED	COPILOT RIGHT	21	COPILOT PHONE JACK
	YLW	COPILOT LEFT	8	
	BLU	COPILOT GND	GND	
	SHLD	NO CONNECTION	GND	NO CONNECTION
PILOT MIC	RED	PILOT PTT	10	PILOT MIC JACK
	YLW	PILOT MIC	23	
	BLU	PILOT GND	2	
	SHLD	NO CONNECTION	GND	NO CONNECTION
COPILOT MIC	RED	COPILOT PTT	16	COPILOT MIC JACK
	YLW	COPILOT MIC	3	
	BLU	COPILOT GND	2	
	SHLD	NO CONNECTION	GND	NO CONNECTION
EFIS AUDIO L	BRN	EFIS AUDIO LEFT	19	SkyView D37 Pin 13
EFIS AUDIO R	GRY	EFIS AUDIO RIGHT	6	SkyView D37 Pin 31
EFIS AUDIO GND	BLK	EFIS AUDIO GND	20	SkyView D37 Pin 30
EFIS DIM	WHT	EFIS DIMMING INPUT	5	SkyView D37 Pin 26
MUSIC IN	RED	MUSIC IN LEFT	24	MUSIC INPUT JACK
	YLW	MUSIC IN RIGHT	11	
	BLU	MUSIC IN GND (LO)	18	
	SHLD	NO CONNECTION	GND	NO CONNECTION
NON-MUTING INPUT	WHT	HIGH	17	USER DEFINED
	WHT/BLU	LOW	20	USER DEFINED
	SHLD	NO CONNECTION	GND	NO CONNECTION
MUTING INPUT	WHT	INPUT (HIGH)	4	USER DEFINED
	WHT/BLU	GND (LOW)	20	USER DEFINED
	SHLD	NO CONNECTION	GND	NO CONNECTION

Thank you for your purchase!

The most up to date documentation is always available online at: doc.dynonavionics.com

For support email: support@dynonavionics.com or call 425-402-0433